

Chopped Strand for BMC

ECS403

Identification

Example : ECS403-6-L
ECS : E-glass Chopped strands
Sizing code : 403
Chopped length (mm) : 6
Filament diameter : 13.7



Product Description

Specially designed for BMC processing . Applied in ceiling, electric switch, lampshade etc..

Product Benefits

- Good flowability
- Good wetting.
- Easy coloring
- Good appearance for fiber and finished goods
- Perfect impact strength

Technical Characteristics


| Compatible Resin | Diameter (μm) | Moisture Content (%) | Loss on Ignition (%) | Bulk Density (g/ cm3) |
|------------------|---------------|----------------------|----------------------|-----------------------|
| / | ISO 1888 | ISO 3344 | ISO 1887 | ISO 15100 |
| UP、VE | ±1 | ≤0.01 | 0.8±0.1 | 0.7±0.15 |

| Product code | Glass Type | Filament diameter[μm] | Chopped length [mm] |
|--------------|------------|-----------------------|---------------------|
| ECS403 | ECT | 13.7 | 6、12 |

Packing

| Package Method | Package weight [kg] | Quantity | Pallet size [mm] Length*width*height |
|-----------------------|---------------------|----------|--------------------------------------|
| Super sack bag | 1000 | 1 pallet | 1140*1140*1100 |
| Poly-plastic film bag | 25 | 40 bags | 850*500*120 |

Pallets illustration



Note: Products can be packed according to the customer's request.

Storage

- If no special requirements, it should be stored in cool and dry place .The recommended temperature range is 10-30℃ ,humidity should be 50 -75%.
- The product should be always kept package encapsulation before use.
- Pallet stacking height should not over 1 layer.



FIBERGLASS