

Chopped Strand for BMC

ECS407

Identification

Example : ECS407-3-K
ECS : E-glass Chopped strands
Sizing code : 407
Chopped length (mm) : 3
Filament diameter : 13



Product Description

This kind is specially designed for BMC processing. Applied in electronic switch 、 car parts、 sanitary ware, etc

Product Benefits

- Good flowability, low fuzz
- Fast wet out and coloring
- Good color of fiber and GFRP
- Excellent comprehensive mechanical properties of GFRP

Technical Characteristics


Compatible Resin	Diameter (μm)	Moisture Content (%)	Loss on Ignition (%)	Bulk Density (g/ cm ³)
/	ISO 1888	ISO 3344	ISO 1887	ISO 15100
UP、 VE	±1	≤0.1	1.65±0.2	±0.15

Product code	Glass Type	Filament diameter[μm]	Chopped length [mm]
ECS407	ECT	13	3、 6、 12、 24、 48

Packing

Package Method	Package weight [kg]	Quantity	Pallet size [mm] Length*width*height
Super sack bag	1000	1 pallet	1140*1140*1100
Poly-plastic film bag	25	40 bags	850*500*120

Pallets illustration



Note: Products can be packed according to the customer's request.

Storage

- If no special requirements, it should be stored in cool and dry place. The recommended temperature range is 10-30°C, humidity should be 50-75%.
- The product should be always kept package encapsulation before use.
- Pallet stacking height should not over 1 layer.



ISO 9001



ISO 14001



OHSAS 18001